

Appl. No.: 10/767,669  
Amdt. dated Apr 16, 2007  
Reply to Office action of Feb 20, 2007

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1-23 (cancel)

Claim 24 (currently amended): A rearview mirror assembly for attachment to a vehicle via a holding tube, the assembly comprising:

a mirror housing including a framing element defining a first recess

configured to attach to the holding tube;

a clamping bracket defining a second recess configured to attach to the holding tube and disposed opposite of the framing element, the first recess of the framing element and the second recess of the clamping bracket cooperating to encase and clamp with the holding tube and releasably attach to each other;

the clamping bracket further configured to fastenably hold a mirror element; wherein,

one of the clamping bracket and the framing element has a hook element and one of the clamping bracket and the framing element has a snap connection, the hook element and the snap connection snap-connectable to secure the framing element and the clamping part clamping bracket together.

Claim 25 (currently amended): The rearview mirror assembly of claim 24 wherein said clamping bracket is a plastic housing having at least a first opening therethrough

Appl. No.: 10/767,669  
Amdt. dated Apr 16, 2007  
Reply to Office action of Feb 20, 2007

and said framing element has at least a second opening therethrough which aligns with said at least first opening, a connector passing through said clamping bracket and said framing element securing said at least a first openings opening of said clamping bracket and said at least a second opening of said framing element aligned and securing said first the first and second recesses with said holding tube.

Claim 26 (currently amended): A rearview mirror assembly ~~for attachment~~ removably attached to a vehicle comprising:

a holding element carried by said vehicle;

a mirror element having a mirror pane attached to a carrier plate;

a positioning apparatus supporting said carrier plate;

a framing having a configured area ~~adapted to engage~~ engaged with said holding element;

a bracket, including an upper strip, ~~strip~~ and a lower strip and a configured area, said configured area being adjacent said upper strip and said lower strip ~~adapted to engage~~ and engaged with said holding element; and

a plurality of connectors ~~adapted to engage~~ engaged with said positioning apparatus, said framing and said bracket securing said framing and said bracket ~~with~~ against said holding element and securing said positioning apparatus with said bracket upper and lower strips of said bracket, ~~Framing; wherein,~~ ~~said mirror assembly is removably attached with said vehicle.~~

Claim 27 (previously presented): The mirror assembly of claim 26 wherein said holding element comprises a first arm separated from a second arm and said configured area

Appl. No.: 10/767,669  
Amdt. dated Apr 16, 2007  
Reply to Office action of Feb 20, 2007

adjacent said upper strip of said bracket is engaged with said first arm and said configured area adjacent said second strip of said bracket is engaged with said second arm.

Claim 28 (previously presented): The mirror assembly of claim 27 wherein said configured area of at least said framing comprises a recess, said recess cooperating with the configured area of said bracket and said upper and lower strips to secure said mirror assembly with said holding arm.

Claim 29 (currently amended): The mirror assembly of claim 26 wherein said framing and said bracket include a ~~hood~~ hook and a snap connection, said hook and said snap connection cooperating to secure said framing and said bracket together.

Claim 30 (previously presented): The mirror assembly of claim 26 wherein said connectors secure said framing and said bracket with each other and said holding arm.

Claim 31 (previously presented): The mirror assembly of claim 26 wherein said connectors secure said positioning apparatus with said bracket.

Claim 32 (previously presented): The mirror assembly of claim 26 including a housing cover and a hook and hook connectors carried by said housing cover and said framing, said hook and hook connectors securing said housing cover with said framing in position covering said bracket.

Claim 33 (currently amended): The rearview mirror assembly of claim 26 wherein, each said configured areas comprise recesses with at least selected of said recesses having area includes at least one of a projection and an indentation, wherein and said holding arm holding element includes at least one of said projections a projection and

Appl. No.: 10/767,669  
Amdt. dated Apr 16, 2007  
Reply to Office action of Feb 20, 2007

Indentations and an indentation, wherein said projections and indentations are positioned to inter-engage when said framing and said bracket are secured about said holding arm holding element securing said framing and said bracket against rotation.

Claim 34 (currently amended): The rearview mirror assembly of claim 26 further comprising a housing cover releasably attached to the framing, the housing cover being made of acrylonitrile butadiene styrene (ABS) and and said framing being made of fiberglass reinforced plastic.

Claim 35 (currently amended): The rearview mirror assembly of claim 26 wherein the carrier plate is acrylonitrile butadiene styrene (ABS) and 30% fiberglass, the carrier plate having a with a thickness of between one and one and one-half millimeters.